

2.9L Whipple Gen 4

| Pump | Hose Size | IC Port Size | GPM |
|------|-----------|--------------|-----|
|------|-----------|--------------|-----|

Average/Standard .625" IC Ports - .75" Hose:

| | | | |
|------------------------------|------|-------|-------|
| DOB POWA Pump | 0.75 | 0.625 | 10.25 |
| Stewart E2512A | 0.75 | 0.625 | 9.75 |
| 13' GT500 Pump | 0.75 | 0.625 | 9 |
| Whipple High Flow (Bosch) | 0.75 | 0.625 | 8.75 |
| Bosch/ Bosch outlet to inlet | 0.75 | 0.625 | 8.5 |
| Bosch/Bosch 180deg | 0.75 | 0.625 | 8 |
| Davies Craig EWP150 | 0.75 | 0.625 | 6.5 |
| 55gpm | 0.75 | 0.625 | 5.75 |
| Rule 2000 | 0.75 | 0.625 | 5.5 |
| Bosch | 0.75 | 0.625 | 5.5 |
| 20gpm | 0.75 | 0.625 | 4.75 |

Average/Standard .625" IC Ports - 1" Hose:

| | | | |
|---------------------|---|-------|-------|
| DOB POWA Pump | 1 | 0.625 | 11.25 |
| Stewart E2512A | 1 | 0.625 | 10.75 |
| Rule 3700 | 1 | 0.625 | 7.5 |
| Davies Craig EWP150 | 1 | 0.625 | 7.25 |

Average/Standard .625" IC Ports - 1.25" Hose:

| | | | |
|----------------|------|-------|------|
| DOB POWA Pump | 1.25 | 0.625 | 16 |
| Stewart E2512A | 1.25 | 0.625 | 15.5 |

| | | | |
|---------------------|------|-------|-------|
| Rule 3700 | 1.25 | 0.625 | 12.5 |
| Davies Craig EWP150 | 1.25 | 0.625 | 12.25 |

Flow Modded .87" Intercooler Ports - 1" hose:

| | | | |
|---------------------|---|------|-------|
| DOB POWA Pump | 1 | 0.89 | 18.5 |
| Stewart E2512A | 1 | 0.89 | 17 |
| Rule 3700 | 1 | 0.89 | 10.25 |
| Davies Craig EWP150 | 1 | 0.89 | 10 |
| 55gpm | 1 | 0.89 | 9.5 |
| Rule 2000 | 1 | 0.89 | 9.25 |

Flow Modded .87" Intercooler Ports - 1.25" hose:

| | | | |
|---------------------|------|------|-------|
| DOB POWA Pump | 1.25 | 0.89 | 23.5 |
| Stewart E2512A | 1.25 | 0.89 | 22 |
| Davies Craig EWP150 | 1.25 | 0.89 | 14 |
| Rule 3700 | 1.25 | 0.89 | 12.75 |
| 55gpm | 1.25 | 0.89 | 12 |
| Rule 2000 | 1.25 | 0.89 | 11.75 |